

BOOM

SEMI-AUTOMATIC ROTATING ARM STRETCH WRAPPING MACHINE FOR UNSTABLE OR HEAVY PRODUCTS

POLUAUTOMATSKE MAŠINE ZA STREČOVANJE SA ROTIRAJUĆOM RUKOM ZA NESTABILNE I TEŠKE PROIZVODE



CONTROL PANEL / KONTROLNI PANEL

Control panel with jog

SETTINGS / KONFIGURACIJA

Arm rotating speed / *Brzina rotiranja*

Top wraps / *Omotavanje na vrhu palete*

Bottom wraps / *Omotavanje na dnu palete*

Upward-downward speed carriage / *Brzina nosača folije gore-dole*

Upward-downward cycle / *Gore-dole ciklus*

Upward or downward cycle / *Ciklus samo gore ili samo dole*

Photocell delay / *Fotočelija za odloženi start*

Manual carriage upward-downward / *Manualno pokretanje nosača folije*

Rotary arm phasing button / *Sinhronizacija rotirajuće ruke*

Carriage height at end cycle / *Podešavanje položaja nosača folije na kraju ciklusa*

CARRIAGE / NOSAČ FOLIJE



CARRIAGE 202 / NOSAČ 202

Carriage with mechanical brake, film tensioning manual adjustable

Nosač folije sa mehaničkom kočnicom za zatezanje folije, podešavanje tenzije ručno

TECHNICAL FEATURES / TEHNIČKE KARAKTERISTIKE

MACHINE / MODEL	BOOM 202
Carriage type / Tip nosača	Mechanical brake / Mehanička kočnica
Film stretch / Zatezanje folije	Manual adjustment / Ručno podešavanje
Pre-stretch / Pre-streč	N/A
Power supply voltage / Napajanje	230 V 1 PH(±15%) 50/60 Hz
Carriage up-down speed Brzina nosača folije gore-dole	2,6÷6 m/min
Arm rotation speed / Brzina rotiranja ruke	7÷11 RPM
Productivity / Produktivnost	20 (pallet/h)
Min product dimension / Minimalna dimenzija pakovanja	LxWxH 500x500x500 mm
Max product dimension Max. dimenzija pakovanja	LxWxH 1200x1200x2000 mm
FILM FEATURES / KARAKTERISTIKE FOLIJE	
Max product dimension / Max. dimenzija	ØxH 275x500 mm
Internal reel diameter / Unutrašnji prečnik hilzne	76 mm
Film thickness / Debljina folije	7÷35 µm
Maximum reel weight Max. težina rolne folije	8 kg

MACHINE LAYOUT / DIMENZIJE U PROSTORU

