

BOOMERANG

AUTOMATIC ROTATING ARM STRETCH WRAPPING MACHINES
AUTOMATSKA MAŠINA ZA STREČOVANJE SA ROTIRAJUĆOM RUKOM



CONTROL PANEL / KONTROL PANEL

7" Touch screen control panel, with user friendly graphic's icons
7", Ekran osetljiv na dodir sa prilagodjenim grafičkim ikonama

PARAMETERS ADJUSTABLE FROM CONTROL PANEL /

PARAMETRI KOJI SE PODEŠAVAJU PREKO KONTROLNOG PANELA

Pre-stretch (212-214) / *Pre-streč (212-214)*

Film tensioning (210-212-214) / *Podešavanje tenzije folije (210-212-214)*

Arm rotating speed / *Brzina rotiranja ruke*

Top wraps-bottom wraps / *Omotavanje na vrhu-omotavanje na dnu*

Upward-downward speed carriage / *Brzina nosača folije gore-dole*

Start from the ground / *Start sa zemlje*

Photocell delay / *Fotočelija za odloženi start*

Altimeter / *Kontrola visine*

Manual carriage upward-downward / *Ručno pokretanje nosača folije*

Manual pressure platen up-down / *Manuelno pokretanje prese*

Cycle recording / *Snimanje ciklusa pakovanja*

CYCLES AND PROGRAMS CUSTOMIZABLE / CIKLUSI PAKOVANJA I PROGRAMI SE MOGU PRILAGODITI

Upward or downward or alternative cycle / *Gore ili dole ili alternativni ciklus*

Top sheet cycle / *Ciklus za foliju na vrhu*

Pressure platen cycle / *Ciklus sa presom*

CARRIAGE / NOSAČ FOLIJE



CARRIAGE 210 / NOSAČ FOLIJE 210

Carriage with electromagnetic brake, film tensioning adjustable from control panel
Nosač folije sa elektromagnetnom kočnicom, tenzija folije podesiva preko kontrolnog panela



CARRIAGE 212 / NOSAČ FOLIJE 212

Carriage with fixed pre-stretch 250%, in option 150%, 200%, 300%.
Film tensioning by load cell, adjustable from control panel
Nosač folije sa fiksnim pre-streč 250%, opciono 150%,200%,300%
Zatezanje folije preko merne ćelije, podešavanje preko kontrolnog panela



CARRIAGE 214 / NOSAČ FOLIJE 214

Carriage with 2 independent motor, variable film pre-stretch from 150% to 400%.
Pre-stretch and film tensioning adjustable from control panel
Nosač folije sa dva nezavisna motora, podešavanje predistezanja od 150% do 400%. Pre-streč istezanje i tenzija folije podešava se preko kontrolnog panela.

BOOMERANG

TECHNICAL FEATURES / TEHNIČKE KARAKTERISTIKE

MACHINE / MODEL	BOOMERANG 210	BOOMERANG 212	BOOMERANG 214
Carriage type / <i>Tip nosača</i>	Electromagnetic power brake / <i>Elektromagnetna kočnica</i>	Power pre-stretch motorized / <i>Motorizovan pre-atreč</i>	2 variable pre-stretch motors / <i>2 nezavisna pre-streč motora</i>
Film stretch / <i>Zatezanje folije</i>	Adjustable from panel / <i>regulacija preko panela</i>		
Pre-stretch / <i>Pre-streč</i>	N/A	250%	150÷400%
Power supply voltage / <i>Napajanje</i>	230 V 1 PH(±15%) 50/60 Hz		
Carriage up-down speed / <i>Brzina nosača folije gore-dole</i>	2,5÷5,5 m/min		
Arm rotation speed / <i>Brzina rotacije ruke</i>	7÷12 RPM		
Productivity / <i>Produktivnost</i>	30 (pallet/h)		
Min product dimension / <i>Min. dimenzija proizvoda</i>	LxWxH 400x400x500 mm		
Max product dimension / <i>Max. dimenzija proizvoda</i>	LxWxH 1400x1400x2000 mm (H 2400-2750 mm OPT)		
FILM FEATURES / KARAKTERISTIKE FOLIJE			
Max product dimension / <i>Max. dimenzija</i>	ØxH 300x500 mm		
Internal reel diameter / <i>Unutrašnji prečnik</i>	76 mm		
Film thickness / <i>Debljina folije</i>	17÷35 µm		
Maximum reel weight / <i>Max. težina folije</i>	20 kg		

MACHINE LAYOUT / DIMENZIJE U PROSTORU

